

# **Serial control RS-232 / RS-485.**



**57 mm high digits. Industrial environment  
Readable from up to 25m  
1 o 2 displaying sides.**

## Application field

It shows data of internal registers from a PLC.

It displays data created from a PC.

It displays in big letters the lecture of voltmeter, temperature regulators, process controllers, etc.

It displays data of users equipment based on microprocessors with RS-232 and RS-485 serial line, such as large scales, electromedecine equipments, etc.

Connection to Modbus ( soon with other buses).

If Host-Link Omron protocol is used, the RS-422 option will be necessary .


## Colour option

Available for models DN-109 and DN-119. It lets you to choose the display colour depending on the input value. The valid colours are: Red, green and yellow.



## Option to display the measures units

Several measure units can be permanently displayed: Kg, Tm, °C, mV, m/s, l/s, or any other unit, as the consumer desires, up to three characters.



## SERIAL LINE INTERFACE CONFIGURATION

The displays includes two push bottoms to configure the protocol and the transmission characteristics: baud rate, parity, data bits and stop bits.

## General specifications


Numeric display Height	57mm
Unity of mesures text Height (optional)	45mm
Viewing	30 meters
Characters distribution	0 a 9, A,b,C,c,d,E,F,H,h,i,J,L,n,o,P,r,U,u [espace] and [point]
Maximum environmental lighting	1000 lux
Maximum environmental lighting. Models (eh)	No applicable
Colour. Red/Green/Yellow	Applicable
Power supply	88 to 264 VAC 47 to 63Hz . Option 24VCC
N° of displaying sides	One or two
Box	Aluminum extruded
Assembly by lateral supports	Which fix to a surface or let in hung
Protocols	Ditel, ISO1745, Modbus, ASCII, Host-Link, S7-200,others
Operating temperature	-20° to 60°C
Storage temperature	-30° to 70°C
Protection level	IP41 (option IP65)

## Dimensions

Digits	3	4	5	6	7	8	9	10
--------	---	---	---	---	---	---	---	----

DN-109	Height = 122mm		Depth = 120mm					
Width in mm	288	288	288	336	382	430	478	526
Width + Option text in mm	288	336	382	430	478	526	574	622

## Reference composition



## EXAMPLES:

### DN-109/4DX

4 digits, DN-109 series display, two sides.

### DN-109/5SX+TV "m/m"

5 digits, DN-109 series display, one side.  
Text option: "m/m" in vinyl

### DN-109Ce/6SX

6 Digits, DN-109 series, one side.  
Red/green/yellow colour display digits. Protection degree IP65.